

1. Unique identification code of the product-type:

The three-layer membrane for waterproofing and damp AlphaProPlus

2. Intended use/es:

Plastic or rubber sheet used on or under floors/ground slabs or in walls to prevent liquid water not under hydrostatic pressure passing from the ground into the internal environment

Sheet used in wall construction or in or under floors or ground slabs to prevent liquid water under hydrostatic pressure passing from the ground into the internal environment or from one section of the structure to another.

3. Manufacturer:

Address: Alpha Dam Sp. z o.o.
Dębowa Łąka 45
87-207 Dębowa Łąka 45

4. System/s of AVCP

System 2+

5. Harmonised standard:

PN-EN 13967: 2012 Flexible sheets for waterproofing – Plastic and rubber damp proof sheets including plastic and rubber basement tanking sheet – Definitions and characteristics

Notified body/ies: 1434, 1488

Certification body/ies: 1023

Institut pro testovani a certifikaci a.s., T. Bati 299, 764 21 Zlin, Czechy

Conducted an inspection of factory and factory production control and inspection surveillance assessment and evaluation on factory production control system 2+ and issued Certificate of Conformity of the Factory Production Control No 1023-CPR-0446 F for AlphaProPlus

	DECLARATION OF PERFORMANCE	Number	35/2016
		Date of issue	13.07.2016
		Page 2 of 2	

6. Declared performance/s:

Essential characteristic	Unit	Performance	
		single	double
Reaction on fire	class	E	E
Watertightness	60 kPa Method B	Watertight	Watertight
Tear resistance:			
- in transverse direction:	N	≥ 400	≥ 400
- in longitudinal direction:	N	≥ 450	≥ 450
Joint strength	N	≥ 400	≥ 400
Resistance to impact	mm Method A	≥ 300	≥ 300
Tensile properties:			
Maximum strength:			
- in longitudinal direction:	N/50mm	≥ 500	≥ 500
- in transverse direction:	N/50mm	≥ 400	≥ 400
Elongation:			
- in longitudinal direction:	%	≥ 400	≥ 400
- in transverse direction:	%	≥ 100	≥ 100
Resistance to static loading	kg Method B	≥ 20	≥ 20
Durability			
- watertightness after artificial ageing	60 kPa method B	Watertight	Watertight
- alkali resistance		no cracks and holes	no cracks and holes
Dangerous substance	-	don't contain	don't contain

7. The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Majek Iwona

Proxy Iwona Majek
Dębowa Łąka, 13 July 2016